

TEC

Industrial

www.tecindustrial.ie | +353 1 457 3533

Email us at: sales@tecindustrial.ie
Unit C3 Weatherwell Business Park
Ninth Lock Road, Clondalkin, Dublin 22
D22 P803, Ireland | Fax: (01) 457 3627



// FLEXOR 2SN/R2AT - MINETUFF

ISO 1436-1 - SAE 100 R2AT - EN 853 2SN

Tube: oil resistant synthetic rubber.

Reinforcement: two high tensile steel braids.

Cover: abrasion, ozone and hydrocarbon resistant synthetic rubber.

MSHA APPROVED

Application: high pressure hydraulic lines, fuel oil, antifreeze solutions, air and water.

Constant operation: -40 °C +100 °C (-40 °F +212 °F)

air max T = +70 °C (+160 °F)

Safety factor: 1:4

Length: random up to 1" - 61 m max over 1"1/4



Item Code	↔			↔		↻		↻		⤵		⬆	
	Dash	mm	in	mm	in	Mpa	psi	Mpa	psi	mm	in	kg/m	lb/ft
1002467	04	6,0	1/4"	14,20	0,56	40,0	5850	160,0	23200	100,0	3,94	0,330	0,23
1002468	05	8,0	5/16"	15,80	0,62	35,0	5000	140,0	20000	115,0	4,53	0,353	0,24
1002469	06	10,0	3/8"	18,20	0,72	33,0	4800	132,0	19200	125,0	4,92	0,463	0,32
1002470	08	13,0	1/2"	21,30	0,84	27,5	4000	110,0	16000	175,0	6,89	0,530	0,36
1002471	10	16,0	5/8"	24,50	0,96	25,0	3630	100,0	14500	200,0	7,87	0,674	0,46
1002472	12	19,0	3/4"	28,60	1,13	21,5	3120	86,0	12500	240,0	9,45	0,852	0,58
1002473	16	25,0	1"	36,60	1,44	16,5	2400	66,0	9600	300,0	11,81	1,224	0,83
1002498	20	32,0	1 1/4"	46,00	1,81	12,5	1820	50,0	7280	420,0	16,54	1,769	1,19
1002474	24	38,0	1 1/2"	52,80	2,08	9,0	1310	36,0	5240	500,0	19,69	2,030	1,37
1002475	32	51,0	2"	65,60	2,58	8,0	1200	32,0	4640	630,0	24,80	2,760	1,86

// SYMBOLS

↔ // INTERNAL DIAMETER

↔ // OUTSIDE DIAMETER

↻ // MAXIMUM WORKING PRESSURE

↻ // MINIMUM BURST PRESSURE

⤵ // MINIMUM BEND RADIUS

⬆ // WALL THICKNESS

⬆ // WEIGHT